

PRODUCT-DETAILS

FH204 AC-40/0.1

FH204 AC-40/0.1 Residual Current Circuit Breaker



| General Information | |
|-----------------------|---|
| Extended Product Type | FH204 AC-40/0.1 |
| Product ID | 2CSF204006R2400 |
| EAN | 8012542895503 |
| Catalog Description | FH204 AC-40/0.1 Residual Current Circuit Breaker |
| Long Description | The RCCBs FH200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous AC and A types is particularly suitable for installation in domestic applications. |

| Technical | |
|---|----------------|
| Standards | IEC 61008 |
| Type of Residual Current | AC type |
| Rated Voltage (U _r) | 230/400 V |
| Rated Operational Voltage | 230 / 400 V AC |
| Rated Insulation Voltage (Ui) | 500 V |
| Rated Impulse Withstand Voltage (U _{imp}) | 4 kV |
| Rated Current (In) | 40 A |
| Rated Residual Current | 100 mA |
| Rated Service Short- Circuit Breaking Capacity (I _{cs}) | 1 kA |
| Maximum Surge Current | 0.25 kA |

FH204 AC-40/0.1

-25...55 °C

| Leakage Current Type | AC |
|----------------------------------|---|
| Rated Frequency (f) | 50 / 60 Hz |
| Power Loss | at Rated Operating Conditions per Pole 3.2 W |
| Number of Poles | 4 |
| Operating Characteristic | Instantaneous |
| Position of Neutral Terminals | Right |
| Mounting Type | DIN rail |
| Options Provided | None |
| Accessories Available | No |
| Rated Cross-Section | 4 - Multi-Wired 1025 mm² 1 - Solid-Core 2525 mm² |

| Environmental | | |
|---------------------|--|--|
| Ambient Temperature | | |
| Ambient Air | | |

Ambient AirOperation -5 ... +40 °CTemperatureStorage -40 ... +70 °CDegree of ProtectionIP2X

RoHS Status Following EU Directive 2011/65/EU
Environmental Refer to RoHS
Information

Technical UL/CSA

Short-Circuit Current 0.1 A Rating (SCCR)

Dimensions

| Width in Number of | 4 |
|----------------------------------|---------|
| Modular Spacings | |
| Product Net Width | 70 mm |
| Product Net Height | 69 mm |
| Product Net Depth / | 85 mm |
| Length | |
| Product Net Weight | 0.38 kg |
| Built-In Depth (t ₂) | 69 mm |

Container Information

| Package Level 1 Units | box 1 piece |
|---------------------------------|---------------|
| Package Level 1 Width | 80 mm |
| Package Level 1 Height | 82 mm |
| Package Level 1 Depth / Length | 94 mm |
| Package Level 1 Gross Weight | 0.415 kg |
| Package Level 1 EAN | 8012542895503 |

Ordering

| Minimum Order Quantity | 1 piece |
|------------------------|------------|
| Customs Tariff Number | 85363030 |
| Country of Origin | Italy (IT) |

| Certificates and Declarations (Document Number) | |
|---|--------------------|
| Declaration of Conformity - CE | 9AKK106713A5603 |
| Environmental Information | Refer to RoHS |
| Instructions and Manuals | No document needed |
| RoHS Information | 2CSC423001K2702 |

| Popular Downloads | |
|--------------------------------------|--------------------|
| Data Sheet, Technical Information | 2CSC400030D0202 |
| Instructions and Manuals | No document needed |

| Classifications | |
|-------------------------------|--|
| ETIM 7 | EC000003 - Residual current circuit breaker (RCCB) |
| ETIM 8 | EC000003 - Residual current circuit breaker (RCCB) |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 85363030 |
| Object Classification Code | F |

Categories





